



## Kardo Mini LED



Multidirectional, accentuating lighting system with adjustable and independent spotlights designed for modular ceilings.

**Ausführung:** Powder painted aluminum frame (standard color: white), aluminum rings, body made of steel sheet in black color, light sources adjustable in two planes.

**Montageart:** Into plaster cardboard and modular ceilings.

**Einspeisung:** 230V

### ELEKTRISCHE PRODUKTDATEN

Leuchtmittel	LED
Nennspannung	220 ... 240 V
mit Leuchtmittel bestückt	Ja

### MECHANISCHE PRODUKTDATEN

Montagearten	Einbaumontage (z.B. Deckeneinbau)
für den Anschluss 3-Phasen Stromschienen	Nein

### INFORMATIONSDATEN

Farbe	weiß
Betriebstemperaturumfang	0 ... 35 °C
drehbar	Ja

### ZERTIFIKATE UND PREISE

Schutzart IP	IP20
CE	Ja
EAC	Ja

### LICHTTECHNISCHE DATEN

Lichtverteilung	Lichtaustritt DI
Abstrahlwinkel / Ausstrahlungswinkel	30 °




### OPTISCHE PRODUKTDATEN

Spiegelraster	Hochglänzend
---------------	--------------

### AUSFÜHRUNGEN

Artikelnummer	Leuchtenanschlussleistung [W]	LED modules	Leuchtenlichtstrom [lm]	Lichtausbeute der Leuchte [lm/W]	Farbtemperatur	Schutzklasse	Gew [kg]
PX1520201 DP001.1166.830. A000	8,5	1x	600	71	3000K	Schutzklasse II, Schutzisolierung	0,1
PX1520208 DP001.1166.840. A000	8,5	1x	620	73	4000K	Schutzklasse II, Schutzisolierung	0,1
PX1520215 DP002.1166.830. A000	15	2x	1080	72	3000K	Schutzklasse I, Schutzleiteranschluss	1,1
PX1520222 DP002.1166.840. A000	15	2x	1120	75	4000K	Schutzklasse I, Schutzleiteranschluss	1,1

## ABMESSUNGEN



Artikelnummer	L [mm]	W [mm]	H [mm]	C [mm]	D [mm]	E [mm]
PX1520201 DP001.1166.830.A000	116	116	81	86	97	79
PX1520208 DP001.1166.840.A000	116	116	81	86	97	79
PX1520215 DP002.1166.830.A000	203	116	81	173	97	79
PX1520222 DP002.1166.840.A000	203	116	81	173	97	79

L = Länge | W = Breite | H = Höhe / Einbautiefe | C = Einbaulänge | D = Einbaubreite | E = Einbautiefe

