



Monza II LED



New luminaire of modern design, based on LED lamps, dedicated for ceiling or suspended mounting. Compact and adjustable Monza II LED is a great solution for both small and bigger spaces, perfect for offices, corridors and many other. The LED luminaires uses diodes of reputable manufacturers. High quality power supply provides high power factor >0,95.

Materials: Powder painted body made of steel sheets and durable polycarbonate, OPAL and microprismatic diffusers made of PMMA.

Installation: Ceiling mounted, suspended.

Accessories: Suspensions type Y (simple, electric).

Power: 230 V

ELECTRICAL DATA

Light source	LED
Type of equipment	AC
Voltage rating	220 ... 240 V
Light source included	Yes
Power factor	0.97

MECHANICAL DATA

Type of installation	Ceiling mounted
Housing material	Steel sheet

INFORMATION

Colour	White
Operating temperature range	-15 ... 40 °C

CERTIFICATES

Degree of protection (IP)	IP20
Class of protection	I
Light source protection	Yes
Energy class	A+
CE	Yes
EAC	Yes

LIGHT DATA

Light colour	White
Color rendering index	84
Light distribution	DI
Class of luminaire	I
Light output degradation	B10
Lumen maintenance	L80
Lifetime	> 72000 h
MacAdam	SDCM 3
Lamp Lumen Maintenance Factor (after 60 000h)	85 %

AVAILABLE VARIANTS

Product code	Luminaire power [W]	LED modules	Louver/shutter	Luminaire luminous flux [lm]	Luminaire's luminous efficacy [lm/W]	Colour temperature	Info	Weight [kg]
PX2250115 EB002.1111.830.A000	27	1x	OPAL	3040	113	3000K	-	2.80
PX2250122 EB002.1111.840.A000	27	1x	OPAL	3100	115	4000K	-	2.80
PX2250227 EB002.1122.830.A000	27	1x	MPRM	3090	114	3000K	-	2.80
PX2250234 EB002.1122.840.A000	27	1x	MPRM	3150	117	4000K	-	2.80
PX2250129 EB003.1111.830.A000	35	1x	OPAL	4060	116	3000K	-	3.90

AVAILABLE VARIANTS

Product code	Luminaire power [W]	LED modules	Louver/shutter	Luminaire luminous flux [lm]	Luminaire's luminous efficacy [lm/W]	Colour temperature	Info	Weight [kg]
PX2250136 EB003.1111.840.A000	35	1x	OPAL	4140	118	4000K	-	3.90
PX2250241 EB003.1122.830.A000	35	1x	MPRM	4130	118	3000K	-	3.90
PX2250248 EB003.1122.840.A000	35	1x	MPRM	4210	120	4000K	-	3.90
PX2250143 EB005.1111.830.A000	42	1x	OPAL	5080	121	3000K	-	4.30
PX2250150 EB005.1111.840.A000	42	1x	OPAL	5180	123	4000K	-	4.30
PX2250255 EB005.1122.830.A000	42	1x	MPRM	5170	123	3000K	-	4.30
PX2250262 EB005.1122.840.A000	42	1x	MPRM	5270	125	4000K	-	4.30
PX2250515 EB002.1111.830.A200	27	1x	OPAL	3040	113	3000K	Emergency module 3h	3.50
PX2250522 EB002.1111.840.A200	27	1x	OPAL	3100	115	4000K	Emergency module 3h	3.50
PX2250627 EB002.1122.830.A200	27	1x	MPRM	3090	114	3000K	Emergency module 3h	3.50
PX2250634 EB002.1122.840.A200	27	1x	MPRM	3150	117	4000K	Emergency module 3h	3.50
PX2250529 EB003.1111.830.A200	35	1x	OPAL	4060	116	3000K	Emergency module 3h	4.60
PX2250536 EB003.1111.840.A200	35	1x	OPAL	4140	118	4000K	Emergency module 3h	4.60
PX2250641 EB003.1122.830.A200	35	1x	MPRM	4130	118	3000K	Emergency module 3h	4.60
PX2250648 EB003.1122.840.A200	35	1x	MPRM	4210	120	4000K	Emergency module 3h	4.60
PX2250543 EB005.1111.830.A200	42	1x	OPAL	5080	121	3000K	Emergency module 3h	5.00
PX2250550 EB005.1111.840.A200	42	1x	OPAL	5180	123	4000K	Emergency module 3h	5.00
PX2250655 EB005.1122.830.A200	42	1x	MPRM	5170	123	3000K	Emergency module 3h	5.00
PX2250662 EB005.1122.840.A200	42	1x	MPRM	5270	125	4000K	Emergency module 3h	5.00
PX2260001 EB006.1133.830.A000	15	2x	PAR	1630	114	3000K	LITE	2.80
PX2260008 EB006.1133.840.A000	15	2x	PAR	1660	116	4000K	LITE	2.80
PX2260015 EB007.1133.830.A000	28	2x	PAR	3260	116	3000K	LITE	5.30
PX2260022 EB007.1133.840.A000	28	2x	PAR	3320	118	4000K	LITE	5.30
PX2260023 EB001.1133.830.A000	27	2x	PAR	3410	126	3000K	-	2.80
PX2260024 EB001.1133.840.A000	27	2x	PAR	3490	129	4000K	-	2.80
PX2260025 EB004.1133.830.A000	51	2x	PAR	6830	134	3000K	-	5.30
PX2260026 EB004.1133.840.A000	51	2x	PAR	6980	137	4000K	-	5.30

DIMENSIONS

	L [mm]	W [mm]	H [mm]	OPAL	MPRM	PAR
<p>23-6-2021</p> <p>PXF Lic</p>	830	223	50	PX2250115 EB002.1111.830.A000 PX2250122	PX2250227 EB002.1122.830.A000 PX2250234	

ACCESSORIES

Electric element



Electrical suspension Y
Pieces in set: 1

PX0922043

Grey

PX0922054

White

Installation element



Simple suspension Y
Pieces in set: 1

PX0922112

grey version



MONZA II LED PAR



